

878 SilverScreen Originals

Non Transparent Metallised



Flame Retardant



Pleated Blinds



Roller Blinds

Superior heat and light control available in 4 transparencies

Features

- Part of the Verosol Core Collection - metallised fabrics developed in Europe, to the highest quality standard
- Offering high performance, independent of colour
- Superior heat and glare control, excellent energy efficient solution
- Woven from 100% Polyester Trevira CS and is inherently flame retardant
- Greenguard Green, Global GreenTagCert™ Gold GreenRate Level A and Oeko-Tex certified
- The Originals Collection features 13 Core colours and 26 Indent colours, available in 4 different transparencies
- Suitable for Pleated Blinds and Roller Blinds

Care Instructions

Verosol fabrics are anti-static and therefore dust repellent. For regular maintenance, use a soft feather duster or vacuum-clean with a soft brush in a low setting.

For more information visit verosol.com.au or call **1800 721 404**



green building council australia
MEMBER 2015-2016

878 SilverScreen Originals

Non Transparent Metallised

Fabric Density	Non Transparent		Anti-Static	Yes
Composition	100% Polyester/Trevira CS, PVC & Formaldehyde free		Antimicrobial	ASTM-E2149-01
Weight	142gsm ± 5%			
Thickness	0.23mm ± 5%			
Width	2400mm ± 50mm			
Colour Fastness	>5 [ISO 105-B02] Metal 8			
Flame Retardancy [AS/NZS 1530.3-1999]	Ignitability Index	0	Range [0-20]	
	Spread of flame Index	0	Range [0-10]	
	Heat evolved Index	0	Range [0-10]	
	Smoke developed Index	0-1	Range [0-10]	
Aluminium Adhesion	ISO 2409	Classification 0		
Corrosion Resistance	Metal layer EN ISO 3231			
Certification	Greenguard Gold	GreenTag Gold	Oeko-Tex 100 Class IV	ISO 9001:2008
	ISO 14001:2004			
Suitable Products	Roller Blinds	Pleated Blinds		

Fabric colour code	0000	0105	0741	0711	0221	0292	0765	0778	0790	0999	0936	0998	0829
Solar transmittance	3%	3%	3%	3%	3%	3%	2%	2%	2%	2%	2%	2%	2%
Solar reflectance outside	68%	68%	68%	68%	68%	68%	68%	68%	68%	68%	68%	68%	68%
Solar absorptance	29%	29%	29%	29%	29%	29%	30%	30%	30%	30%	30%	30%	30%
Luminous transmittance [VLT]	3%	2%	2%	2%	2%	2%	1%	1%	0.6%	0.3%	1%	0.3%	0.2%
UV transmittance	1%	1%	1%	1%	1%	1%	1%	1%	0%	0%	0%	0%	0%
Openness factor (nominal)	0%	0%	0%	0%	0%	0%	0%	0%	0%	0%	0%	0%	0%
Ra (colour rendering index)	99	95	92	94	94	94	78	75	70	98	93	75	70

Glazing Type - Single 4mm Clear Glass

Visible light transmittance	3%
G-value / Solar heat gain coefficient	24%
Shading coefficient	28%
U-value (W/m²K)	2.0

Glazing Type - High Performance Glazing

Visible light transmittance	2%
G-value / Solar heat gain coefficient	17%
Shading coefficient	20%
U-value (W/m²K)	0.8

Colour Range

