
Verosol

CasaSheer Curtain Fabric

Opulent Living





Designer: Christian Zuzunaga

Luxury designer decorative sheer curtain fabric

Features

- Part of the Verosol Opulent Living Collection Drapery fabrics developed to the highest quality standards
- Casa is a plain woven sheer with shiny melange yarns offering exceptional colour depth
- Casa features bright specs of colour, such as blue, green or pink, which are intermingled with understated neutral tones, resulting in a unicoloured appearance from a distance but up-close reveals a rich yet delicate colours
- Woven from 100% Trevira CS, Casa ensures soft drapability and easy care
- Casa is inherently flame retardant making it ideal for both residential and commercial applications
- Casa was designed by acclaimed Barcelona based designer Christian Zuzunaga

Cleaning and care

\60\ Wash at max. 60°C, mild process, drip dry

Do not bleach

Do not tumble dry

Iron at medium temperature (max. 150°C)

(P) Professional dry cleaning with tetrachloroethylene, normal process

For more information visit verosol.com.au or call 1800 721 404







Casa

Sheer Curtain Fabric

Fabric Density	Sheer	Weighted Hem - NO		
Composition	100% Trevira CS	Formaldehyde free	•••••	•••••••••••••••••••••••••••••••••••••••
Weight	510g/lin mtr	***************************************	•••••	•••••
Width	3000mm	Continuous	Nominal roll size	35 linneal metres
Pattern	Solid	***************************************	•••••	•••••
Yarn type	Filament	***************************************	•	•••••
Binding	Plain	•••••		••••••••••••
Colour Fastness	Light [ISO 105-B02] 6 - 7	•••••		•••••••••••••••••••••••••••••••••••••••
Possible Shrinkage	1%			
Flame Retardancy [AS/NZS 1530.3-1999]	Ignitability Index	0 Range [0-20]		•••••
	Spread of flame Index	0 Range [0-10]	•	
	Heat evolved Index	0-1 Range [0-10]	•	
	Smoke developed Index	0 Range [0-10]		
[International Standards]	BS 5867 Part 2 Type B	DIN 4102 B1 NF P 92 507 M1	EN 13 773 class 1 UNI 9177 Class 1	IMO FTP Code 2010:Part 7
Certification	Greenguard	EPD to EN15804	HPD 2.1	REACH
Aiflow Resistance [EN 29053]	Airflow Resistance of R _s = 589 Pa s/m			
Sound Absorption [EN ISO 354]	Report available upon request			
Designer	Christian Zuzunaga			
Manufactured in	Netherlands			
Cleaning	<u></u>	***************************************	•••••	•••••
Suitable Products	Curtains	***************************************	•••••	•••••
• • • • • • • • • • • • • • • • • • • •	• • • • • • • • • • • • • • • • • • • •	• • • • • • • • • • • • • • • • • • • •	• • • • • • • • • • • • • • • • • • • •	• • • • • • • • • • • • • • • • • • • •





Care: \60/ \ \ □ \ □ \