

400 VeroCell

Blockout Metallised



Pleated Blinds

High performance blockout for room darkening and insulation

Features

- Part of the Verosol Core Collection - metallised fabrics developed in Europe, to the highest quality standard
- Cellular design traps air within each cell, creating an effective insulation barrier
- Metallised lining within each cell provides superior insulation
- White base colour on the backing regardless of the colour providing a uniform look from the outside
- No visible holes – ideal where complete room darkening is required, such as bedrooms and theatre rooms
- Greenguard Gold and Oeko-Tex certified
- Suitable for Pleated Blinds

Care Instructions

For regular maintenance, use a soft feather duster or vacuum-clean with a soft brush in a low setting.

For more information visit verosol.com.au or call **1800 721 404**



Management System
ISO 9001:2015
ISO 14001:2015
www.tuv.com
ID 3108621700



400 VeroCell

Blockout Metallised

Fabric Density	Blockout		
Composition	100% Polyester		
Weight	166gsm ± 5%		
Thickness	0.19mm ± 5%		
Width	3000mm		
Colour Fastness	4 - 5 [ISO 105 B02]		
Flame Retardancy	Non Fire Retardant		
Certification	Oeko-Tex 100 Class IV	ISO 9001:2008	ISO 14001:2004
Suitable Products	Pleated Blinds		

Fabric colour code	7610
Solar transmittance	0%
Solar reflectance outside	65%
Solar absorptance	35%
UV transmittance	0%
Openness factor (nominal)	0%





















Glazing Type - Single 4mm Clear Glass

Visible light transmittance	0%
G-value / Solar heat gain coefficient	14%
Shading coefficient	16%
U-value (W/m ² K)	1.6
R-value (W/m ² K)	0.62

Glazing Type - High Performance Glazing

Visible light transmittance	0%
G-value / Solar heat gain coefficient	14%
Shading coefficient	16%
U-value (W/m ² K)	0.7
R-value (W/m ² K)	1.42

Colour Range

										External
										Internal